

View Online at https://aerobasegroup.com/nsn/5935-01-027-3066

| Body Material:   |
|--|
| Plastic  |
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Body Style:  |
| Top mount w/studs  |
| Overall Length:  |
| 1.250 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.124 inches   |
| Overall Height:  |
| 0.531 inches   |
| Overall Width:   |
| 0.390 inches   |
| Mounting Slot Width:   |
| Between 0.138 inches and 0.146 inches                                    |
| Body Mounting Hole Accommodation Length:                                 |
| 0.812 inches   |
| Body Mounting Hole Accommodation Width:                                  |
| 0.438 inches   |
| Distance Between Mounting Facility Centers:                              |
| 1.000 inches   |
| Mounting Hole Style:   |
| Rectangular, w/external slots  |
| Contact Maximum Current Rating In Amps:                                  |
| 3.0  |
| Contact Material:  |
| Phosphor bronze  |
| Contact Surface Treatment:   |
| Gold and silver  |
| Accommodated Contact Quantity:   |
| 8  |
| Polarization Type:   |
| Colored dot  |
| Mounting Method:   |
| Threaded stud  |
| Mounting Type For Which Designed:  |
| Chassis  |
| Thready Qty Per Inch (tpi):  |
| 40   |



**Thread Size:** 0.112 inches **Contact Position Arrangement Style:** Dual in line **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.008 gold grains, troy and 0.008 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unc **Terminal Type And Quantity:** 8 tab, solder lug Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A02300