# NSN 5935-01-027-3085

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-027-3085

#### Body Style:

Straight shape, internal coupling w/strain relief

**Body Length:** 

3.900 inches

## **Overall Diameter:**

1.750 inches

### **Environmental Protection:**

Moisture resistant

#### Cable Entrance Diameter:

0.894 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

24-61 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

### Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

#### Polarization Method:

Keyway or multiple keyway

#### Insert Position In Deg:

270.0

#### Shell Type:

Solid

## **Connector Locking Method:**

Bayonet pin

## **Connector Cable Strain Relief Method:**

Cable clamp

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## Contact Surface Treatment:

Gold single mating end single contact grouping and silver single mating end single contact grouping

## **Insert Material:**

Plastic single mating end

## **Terminal Type:**

Crimp single mating end single contact grouping

## Shell Material:

Aluminum alloy

## Shell Surface Treatment:

Cadmium and chromate

# NSN 5935-01-027-3085

Electrical Plug Connector - Page 2 of 2



**Included Contact Quantity:** 61 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.061 gold grains, troy and 0.061 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0