NSN 5935-01-027-3087

Cadmium and chromate

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-027-3087

Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
3.900 inches
Overall Diameter:
1.750 inches
Environmental Protection:
Moisture resistant
Cable Entrance Diameter:
0.894 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
24-61 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Shell Type: Solid
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Bayonet pin
Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method:
Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp
Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location:
Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping
Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material:
Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping
Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material:
Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic single mating end
Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic single mating end Terminal Type:
Solid Connector Locking Method: Bayonet pin Connector Cable Strain Relief Method: Cable clamp Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping and silver single mating end single contact grouping Insert Material: Plastic single mating end Terminal Type: Crimp single mating end single contact grouping

NSN 5935-01-027-3087

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

61 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.061 gold grains, troy and 0.061 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0