NSN 5935-01-027-3101

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-027-3101

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 1.277 inches and 1.327 inches
Overall Diameter:
Between 1.455 inches and 1.475 inches
Environmental Protection:
Pressure proof and moisture resistant and vibration resistant
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
18-21 f03 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thready Qty Per Inch (tpi):
28
Thread Size:
1.125 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping

NSN 5935-01-027-3101Electrical Plug Connector - Page 2 of 2



Shell Material:	
Aluminum alloy 6061	
Shell Surface Treatment:	
Chromium	
Shell Material Specification:	
Qq-a-367, t6 federal specification single material response	
Included Contact Quantity:	
21 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.021 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-mil-c-81511 specification (includes engineering type bulletins, brochures,	etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade pu	ublications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown	n as "typical", "average", "", etc.).
Thread Series Designator:	
Un	
Specification Data:	
81349-mil-c-81511/46 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	