NSN 5935-01-027-3154

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-027-3154

Body Style:

Straight shape, flush mount

Overall Length:

1.326 inches

Overall Height:

Between 3.060 inches and 3.090 inches

Overall Width:

Between 3.845 inches and 3.875 inches

Environmental Protection:

Solvent resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 2.778 inches and 2.788 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 3.286 inches and 3.306 inches

Distance From Mounting Shoulder To Front Face:

Between 0.050 inches and 0.070 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

8 1st mating end

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Polarization Method:

2 polarization posts

Shell Type:

Solid

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene 1st mating end or plastic diallyl phthalate 1st mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 2 military specification single treatment response all mating ends all contact groupings

Terminal Type:

Crimp all mating ends all contact groupings

Shell Material:

Aluminum alloy 380.0

Shell Surface Treatment:

Cadmium

NSN 5935-01-027-3154

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-591, alloy 380 federal specification single material response

Insert Material Specification:

Mil-p-19833, ty gdi-30f military specification 1st material response all mating ends

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.287 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.