## NSN 5935-01-027-5345

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-027-5345

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

5.620 inches

**Overall Height:** 

0.800 inches

**Overall Width:** 

0.594 inches

**Unthreaded Mounting Hole Diameter:** 

0.128 inches

**Distance Between Mounting Facility Centers:** 

5.352 inches

**Board Accommodated Length:** 

5.030 inches single board

**Board Accommodated Width:** 

0.062 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

8.5 single mating end single contact grouping

**Polarization Method:** 

Contact to contact polarizing keys

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-750 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, ty sdg-30f military specification single material response single mating end

**Included Contact Quantity:** 

47 single mating end single contact grouping

## NSN 5935-01-027-5345

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.047 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):