NSN 5935-01-028-1958

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-028-1958

Body Style: Straight shape **Overall Length:** 0.625 inches **Overall Height:** 0.576 inches **Overall Width:** 0.437 inches **Mating End Quantity: Contact Position Arrangement Style:** 6 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 5.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 250.0 single mating end all contact groupings **Connector Locking Method:** Friction **Operating Tempurature Rating:** Between -40.0 degrees celsius and 105.0 degrees celsius **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings **Insert Material:** Plastic polyamide single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end all contact groupings **Criticality Code Justification:** Feat **Terminal Type:** Printed circuit single mating end all contact groupings **Included Contact Quantity:** 5 single mating end 2nd contact grouping **Included Contact Type:**

morauda comaci Typo.

Round socket single mating end 1st contact grouping

Special Features:

Contact 5 is a socket

NSN 5935-01-028-1958

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.006 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.