NSN 5935-01-028-3329

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-028-3329 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** Between 0.730 inches and 0.740 inches **Overall Diameter:** 1.556 inches **Environmental Protection:** Humidity resistant and shock proof and vibration resistant and salt water resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 22-5 single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 1st contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 900.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 1250.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:**

Internally threaded coupling ring

Thread Length:

0.531 inches

Thread Size:

1.250 inches and 1.375 inches

Terminal Location:

Back single mating end all contact groupings

Insert Material:

Plastic epoxy single mating end

NSN 5935-01-028-3329

No Fiig: A039b0

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Material Specification:
Qq-a-367 federal specification single material response
Included Contact Quantity:
4 single mating end 2nd contact grouping
Included Contact Type:
Round socket single mating end all contact groupings
Test Data Document:
81349-mil-c-83723 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef and unef
Specification Data:
81349-mil-c-83723/23 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization: