NSN 5935-01-028-3522

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-028-3522 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Height:** 2.250 inches **Overall Width:** 2.250 inches **Unthreaded Mounting Hole Diameter:** 0.173 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.750 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.750 inches **Distance From Mounting Shoulder To Front Face:** 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 32-414 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 110.0 Shell Type: Solid **Connector Locking Method:**

18

Externally threaded shell Thready Qty Per Inch (tpi):

NSN 5935-01-028-3522

Electrical Receptacle Connector - Page 2 of 2



Thread Size:
2.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Included Contact Quantity:
52 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.052 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.