

View Online at <https://aerobasegroup.com/nsn/5935-01-028-5772>

Body Style:

Straight shape, internal coupling

Overall Length:

1.020 inches

Overall Diameter:

0.859 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

Oct-98 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

14.0 and 100.0 and 128.0 and 228.0 and 265.0

Shell Type:

Potting

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Potting type

Operating Temperature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

6 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.030 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms27473 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.