Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-028-5804

Thread Class:
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
1.562 inches
Overall Height:
0.850 inches
Overall Width:
0.438 inches
Environmental Protection:
Moisture resistant and vibration proof
Distance Between Mounting Facility Centers:
1.250 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:
Mil-m-14 military specification single material response single mating end or mil-p-19833, type gdi-30f military specification single material
response single mating end
Included Contact Quantity:

20 single mating end single contact grouping



Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28748 government specification

Shelf Life:

N/a

Unit Of Measure:

--Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.