## NSN 5935-01-028-5827

**Shell Surface Treatment:** 

Cadmium

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-028-5827 **Body Style:** Straight shape **Overall Length:** 2.729 inches **Overall Height:** 0.536 inches **Overall Width:** 0.494 inches **Environmental Protection:** Heat resistant and weather resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 2.500 inches **Mating End Quantity: Contact Position Arrangement Style:** 37 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204, type 1 military specification single treatment response single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy

# NSN 5935-01-028-5827

Electrical Receptacle Connector - Page 2 of 2



### **Shell Surface Treatment Specification:**

Qq-p-416, type 2 federal specification single treatment response

### **Shell Material Specification:**

Qq-b-626 federal specification single material response

### **Included Contact Quantity:**

37 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.037 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.