

View Online at <https://aerobasegroup.com/nsn/5935-01-028-6559>

Body Style:

Straight shape

Overall Diameter:

1.375 inches

Environmental Protection:

Fireproof and salt water resistant and shock resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

3 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

125.0 single mating end all contact groupings

Contact Maximum Dc Voltage Rating In Volts:

250.0 single mating end all contact groupings

Polarization Method:

Contact

Connector Locking Method:

Contact twistlock

Connector Cable Strain Relief Method:

Cord protector

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper single mating end all contact groupings or copper alloy single mating end all contact groupings

Terminal Type:

Screw single mating end all contact groupings

Included Contact Quantity:

1 single mating end 3rd contact grouping

Test Data Document:

81348-wc596 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-wc596/49 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0