

View Online at <https://aerobasegroup.com/nsn/5935-01-028-9408>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Hood, top opening w/clamp

**Overall Length:**

1.560 inches

**Overall Width:**

0.460 inches

**Environmental Protection:**

Corrosion resistant and moisture resistant and shock proof and vibration resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

20 20-20 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

13.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Shell Type:**

Hood, top opening

**Connector Locking Method:**

Jackscrew-socket

**Connector Cable Strain Relief Method:**

Cable clamp

**Thread Size:**

0.138 inches and 0.138 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Gold

**Shell Material Specification:**

Qq-a-250 federal specification single material response

**Insert Material Specification:**

Mil-m-19833 military specification single material response single mating end

**Included Contact Quantity:**

20 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Shell surface gold

**Precious Material And Weight:**

0.100 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc and unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-m-19833 spec.