NSN 5935-01-028-9488

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-028-9488

Body Style: Straight type **Overall Length:** 1.090 inches Overall Width: 0.245 inches **Unthreaded Mounting Hole Diameter:** 0.078 inches **Distance Between Mounting Facility Centers:** 0.950 inches **Mating End Quantity: Contact Position Arrangement Style:** 1 row of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Nickel single mating end single contact grouping and gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Contact Material Specification:** Qq-b-750, comp a federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end **Included Contact Quantity:** 7 single mating end single contact grouping **Included Contact Type:**

Precious Material And Location:

Hermaphrodite single mating end single contact grouping

Contact surfaces gold

NSN 5935-01-028-9488

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Weight:
0.007 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.