

View Online at <https://aerobasegroup.com/nsn/5935-01-029-2483>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

Between 1.770 inches and 1.800 inches

**Overall Height:**

0.692 inches

**Overall Width:**

0.340 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.125 inches and 0.131 inches

**Distance Between Mounting Facility Centers:**

1.531 inches

**Board Accommodated Length:**

1.098 inches single board

**Board Accommodated Width:**

0.062 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

830.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1270.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Insert Material Specification:**

Mil-p-19833 military specification single material response single mating end

**Included Contact Quantity:**

6 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.006 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-p-19833 spec.