## NSN 5935-01-029-2489

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-029-2489

**Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.660 inches **Overall Diameter:** 0.312 inches **Distance From Mounting Shoulder To Front Face:** 0.500 inches **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **End Application:** Support equipment, b-52 aircraft; aircraft, thunderbolt ii, a-10 Thready Qty Per Inch (tpi): 36 and 36 **Thread Size:** 0.250 inches and 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## NSN 5935-01-029-2489

Electrical Receptacle Connector - Page 2 of 2



Criticality Code Justification:
Feat
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end single contact grouping
Shell Material:
Steel comp 303
Shell Surface Treatment:
Gold
Shell Surface Treatment Specification:
Mil-g-45204 military specification single treatment response
Shell Material Specification:
Qq-s-763, class 303, cond a federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Special Features:
Weapon system essential
Precious Material And Location:
Contact and shell surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns and uns
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.