Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-029-2489

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.660 inches
Overall Diameter:
0.312 inches
Distance From Mounting Shoulder To Front Face:
0.500 inches
Mounting Facility Thickness:
0.125 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
End Application:
Support equipment, b-52 aircraft; aircraft, thunderbolt ii, a-10
Thready Qty Per Inch (tpi):
36 and 36
Thread Size:
0.250 inches and 0.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Nil a 45004 million on a life the single tester of second second single methods and single

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-01-029-2489

Electrical Receptacle Connector - Page 2 of 2



Criticality Code Justification:

Feat

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

Shell Surface Treatment:

Gold

Shell Surface Treatment Specification:

Mil-g-45204 military specification single treatment response

Shell Material Specification:

Qq-s-763, class 303, cond a federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket single mating end single contact grouping

Special Features:

Weapon system essential

Precious Material And Location:

Contact and shell surfaces gold

Precious Material And Weight:

0.010 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.