
NSN 5935-01-029-4029

Tip Jack - Page 1 of 2

Thread Class:





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Red **Body Style:** Threaded bushing mounted **Overall Length:** 0.906 inches Mounting Bushing Length: 0.469 inches **Body Length:** 0.656 inches **Overall Diameter:** 0.438 inches **Bushing Accommodation Hole Shape:** Round w/double flat Maximum Voltage Rating In Volts: 1000.0 ac Accommodated Finger Type: Banana cross cut single finger **Finger Accommodation Diameter:** 0.161 inches single finger Finger Accommodation Length: 0.563 inches single finger **Bushing Thru-hole Accommodation Length:** 0.250 inches **Bushing Thru-hole Accommodation Width:** 0.313 inches **Capacitance In Picofarads:** 5.0 **Current Rating In Amps:** 15.0 Mounting Facility Type And Quantity: 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.312 inches

NSN 5935-01-029-4029

Tip Jack - Page 2 of 2



Terminal Type:

Turret

Material:

Plastic insulator

Material:

Plastic insulator

Surface Treatment:

Tin spring

Surface Treatment:

Tin spring

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A03400