Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-029-4088

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
2.000 inches
Overall Width:
0.750 inches
Environmental Protection:
Moisture proof and vibration resistant
Distance Between Mounting Facility Centers:
1.688 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
34 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Length:
0.320 inches
Thread Size:
0.112 inches and 0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping
Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end



Included Contact Quantity:

34 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.034 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc and unc

Specification Data:

81349-mil-c-28748/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.