Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-029-4750

Body Style:

Straight shape, rectangular

Overall Length:

1.163 inches

Overall Height:

1.090 inches

Overall Width:

2.275 inches

Environmental Protection:

Moisture proof and vibration resistant

Unthreaded Mounting Hole Diameter:

0.149 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.900 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

52 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

13.0 single mating end single contact grouping

Polarization Method:

Polarization boss

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Crimp single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

Included Contact Quantity:

52 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold



Precious Material And Weight:

0.052 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-28748 government specification

Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.