

View Online at <https://aerobasegroup.com/nsn/5935-01-029-6425>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle, shape, internal coupling

Overall Length:

1.218 inches

Overall Height:

2.000 inches

Overall Diameter:

Between 0.588 inches and 0.615 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Tnc single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

11000.0 megahertz single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

120.0 and 144.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Size:

0.438 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.