mating end



View Online at https://aerobasegroup.com/nsn/5935-01-029-6444

| Thread Class: |
|--|
| 2a and 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Hood, top opening w/clamp |
| Overall Length: |
| 2.000 inches |
| Overall Height: |
| 2.467 inches |
| Overall Width: |
| 0.828 inches |
| Cable Entrance Diameter: |
| 0.340 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 34 single mating end |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Hood, top opening |
| Connector Locking Method: |
| Jackscrew-socket |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thread Size: |
| 0.138 inches and 0.138 inches |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Shell Surface Treatment Specification: |
| Mil-a-8625, type 1 military specification single treatment response |
| Shell Material Specification: |
| Qq-a-250 federal specification single material response |
| Insert Material Specification: |
| Mil-m-14, sdg-f military specification single material response or mil-p-19833, gdi-30f military specification single material response single |



Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.