

View Online at <https://aerobasegroup.com/nsn/5935-01-029-8623>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external/internal coupling

**Overall Length:**

1.438 inches

**Overall Diameter:**

0.625 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Tps 2nd mating end

**Contact Removability:**

Nonremovable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

50.0 all mating ends all contact groupings

**Contact Maximum Ac Voltage Rating In Volts:**

250.0 all mating ends all contact groupings

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 all mating ends all contact groupings

**Contact Maximum Frequency Rating:**

10000.0 megahertz all mating ends all contact groupings

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch and internally threaded coupling ring

**Thread Size:**

0.625 inches

**Insert Material:**

Plastic all mating ends

**Included Contact Quantity:**

1 2nd mating end all contact groupings

**Included Contact Type:**

Coaxial socket all mating ends all contact groupings

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0