## NSN 5935-01-029-8962

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-029-8962

| Body Style:  |
|--|
| Straight shape threaded  |
| Overall Length:  |
| 0.473 inches   |
| Overall Diameter:  |
| 0.797 inches   |
| Environmental Protection:  |
| Moisture resistant and salt water resistant and vibration proof                                    |
| Distance From Mounting Shoulder To Front Face:   |
| 0.317 inches   |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| 13-oct single mating end   |
| Contact Removability:  |
| Nonremovable single mating end single contact grouping   |
| Polarization Method:   |
| Keyway or multiple keyway  |
| Insert Position In Deg:  |
| 0.0  |
| Shell Type:  |
| Solid  |
| Connector Locking Method:  |
| Bayonet latch  |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Material:  |
| Nickel alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Tin single mating end single contact grouping and copper single mating end single contact grouping |
| Terminal Type:   |
| Solder well single mating end single contact grouping  |
| Shell Material:  |
| Steel  |
| Shell Surface Treatment:   |
| Tin  |
| Shell Surface Treatment Specification:   |
| Mil-t-10727 military specification single treatment response                                       |
| Included Contact Quantity:   |
| 13 single mating end single contact grouping   |

**Included Contact Type:** 

Round pin single mating end single contact grouping

## NSN 5935-01-029-8962

Electrical Receptacle Connector - Page 2 of 2



| Solder flange mounted |
|-----------------------|
| Shelf Life:           |
| N/a                   |
| Unit Of Measure:      |
|                       |
| Demilitarization:     |

**Special Features:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-t-10727 spec.