NSN 5935-01-029-8963

Thread Class:

Right-hand **Body Style:**

Thread Direction:

Overall Length: 4.875 inches

Straight edge type w/card guide

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-029-8963

Overall Height:
3.277 inches
Overall Width:
0.343 inches
Unthreaded Mounting Hole Diameter:
0.112 inches
Distance Between Mounting Facility Centers:
4.031 inches
Board Accommodated Length:
3.277 inches single board
Threaded Device Type:
Mounting hole
Board Accommodated Width:
0.076 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of independent contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Contact to contact polarizing keys
Thread Size:
0.112 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Plastic diallyl phthalate single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic polycarbonate single mating end

NSN 5935-01-029-8963

Electrical Receptacle Connector - Page 2 of 2



T	erm	inal	Typ	oe:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end single contact grouping

Included Contact Quantity:

44 single mating end single contact grouping

Included Contact Type:

Bifurcated spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.036 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.