# NSN 5935-01-029-8973

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-029-8973

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight type
Overall Length:
3.100 inches
Overall Height:
1.049 inches
Overall Width:
Between 0.289 inches and 0.302 inches
Environmental Protection:
Salt water resistant and shock resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.086 inches
Distance Between Mounting Facility Centers:
2.950 inches
Threaded Device Type:
Mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Guide pin/socket
Thready Qty Per Inch (tpi):
56
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

**Contact Surface Treatment Specification:** 

Plastic diallyl phthalate single mating end

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

## NSN 5935-01-029-8973

Electrical Receptacle Connector - Page 2 of 2



Terminal	Type:
----------	-------

Wire wrap single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

## **Included Contact Quantity:**

54 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

### **Precious Material And Weight:**

0.054 gold grains, troy

#### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unc

## **Specification Data:**

81349-mil-c-55302/52 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.