Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-029-9620

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
0.531 inches
Overall Diameter:
0.562 inches
Environmental Protection:
Humidity resistant and shock resistant and thermal shock resistant and vibration resistant
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
9 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Latching ring
Thready Qty Per Inch (tpi):
20
Thread Size:
0.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c military specification 1st treatment response single mating end single contact grouping

NSN 5935-01-029-9620 Electrical Plug Connector - Page 2 of 2



Terminal 1	
	single mating end single contact grouping
	aterial Specification:
-	ederal specification single material response single mating end single contact grouping
Shell Mate	rial:
Aluminum	alloy
Shell Surf	ace Treatment:
Cadmium	
Shell Surf	ace Treatment Specification:
Qq-p-416,	type 2, cl 1 federal specification single treatment response
Insert Mat	erial Specification:
Mil-m-14, t	y sdg-f military specification single material response single mating end
Included (Contact Quantity:
9 single ma	ating end single contact grouping
Included (Contact Type:
Round soc	ket single mating end single contact grouping
Precious I	Material And Location:
Contact su	rfaces gold
Precious I	Naterial And Weight:
0.009 gold	grains, troy
Precious I	Material:
Gold	
Thread Se	ries Designator:
Unf	
Shelf Life:	
N/a	
Unit Of Me	easure:
Demilitariz	zation:
No	
Fiig:	
A039b0	
Mil-std (m	ilitary Standard):
Mil-g-4520	4 spec.