NSN 5935-01-030-1864



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-030-1864 **Body Style:** Straight shape, external coupling **Overall Length:** 1.586 inches **Overall Height:** 1.578 inches **Overall Width:** 1.578 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** 0.556 inches **Mating End Quantity: Contact Position Arrangement Style:** 26 number 20 single mating end **Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping

Shell Material: Aluminum alloy

Shell Surface Treatment:

Cadmium

NSN 5935-01-030-1864

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Included Contact Quantity:

6 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.031 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0