NSN 5935-01-030-5110

Thread Class:

Right-hand

Thread Direction:

2b

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-030-5110

Body Style:
Straight edge type w/mounting flange
Overall Length:
7.615 inches
Overall Height:
0.564 inches
Overall Width:
0.500 inches
Environmental Protection:
Vibration resistant
Distance Between Mounting Facility Centers:
7.302 inches
Board Accommodated Length:
6.825 inches single board
Threaded Device Type:
Mounting hole
Board Accommodated Width:
Between 0.054 inches and 0.071 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of independent contacts inserted board single mating end
2 rows of independent contacts inserted board single mating end Contact Removability:
Contact Removability:
Contact Removability: Nonremovable single mating end single contact grouping
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Contact to contact polarizing keys
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Contact to contact polarizing keys Thread Size:
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Contact to contact polarizing keys Thread Size: 0.112 inches
Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 5.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Contact to contact polarizing keys Thread Size: 0.112 inches Terminal Location:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Contact Surface Treatment:

NSN 5935-01-030-5110

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Tab, solder lug single mating end single contact grouping
Included Contact Quantity:
86 single mating end single contact grouping
Included Contact Type:
Bifurcated accordian leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.086 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0