

View Online at <https://aerobasegroup.com/nsn/5935-01-030-5110>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

7.615 inches

**Overall Height:**

0.564 inches

**Overall Width:**

0.500 inches

**Environmental Protection:**

Vibration resistant

**Distance Between Mounting Facility Centers:**

7.302 inches

**Board Accommodated Length:**

6.825 inches single board

**Threaded Device Type:**

Mounting hole

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Polarization Method:**

Contact to contact polarizing keys

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:**

86 single mating end single contact grouping

**Included Contact Type:**

Bifurcated accordian leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.086 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0