NSN 5935-01-030-5686



Connector Adapter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-030-5686 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/flange **Overall Length:** 2.125 inches **Overall Height:** 1.375 inches **Overall Width:** 1.375 inches **Environmental Protection:** Fuel resistant and oil resistant **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.124 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.062 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.062 inches **Distance From Mounting Shoulder To Front Face:** Between 0.975 inches and 0.985 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 18-11 all mating ends **Contact Removability:** Nonremovable 2nd mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 1st mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 500.0 2nd mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 2nd mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 170.0

Shell Type:

Solid

NSN 5935-01-030-5686

Connector Adapter - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.625 inches
Thread Size:
1.125 inches
Contact Surface Treatment:
Gold all mating ends all contact groupings
Insert Material:
Plastic diallyl phthalate all mating ends
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl c federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-m-14 military specification single material response all mating ends
Included Contact Quantity:
5 2nd mating end all contact groupings
Included Contact Type:
Round socket 2nd mating end all contact groupings
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.