Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-030-7696

# Thread Class: 2a and 2b

Thread Direction:

Right-hand and right-hand

# Body Style:

Straight shape, internal coupling

## **Overall Length:**

2.125 inches

#### **Overall Diameter:**

2.719 inches

## **Environmental Protection:**

Moisture resistant and vibration resistant and salt water resistant

## **Threaded Device Type:**

Back shell and coupling facility

## Mating End Quantity:

1

# Contact Position Arrangement Style:

40-56 single mating end

# **Contact Removability:**

Removable single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

288.0

Shell Type:

Solid

## Connector Locking Method:

Internally threaded coupling ring

# Thread Length:

0.664 inches

## Thready Qty Per Inch (tpi):

16 and 16

# Thread Size:

2.500 inches and 2.500 inches

## **Terminal Location:**

Back single mating end single contact grouping

## **Insert Material:**

Plastic silicone mineral filled single mating end

NSN 5935-01-030-7696

Electrical Plug Connector - Page 2 of 2



**Terminal Type:** 

Crimp single mating end single contact grouping

Shell Material:

Aluminum

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

#### **Included Contact Quantity:**

85 single mating end single contact grouping

#### Included Contact Type:

Round socket single mating end single contact grouping

## **Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

Un and un

#### **Specification Data:**

81349-mil-c-5015 government specification

Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

#### Fiig:

A039b0