NSN 5935-01-031-1715

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-031-1715 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.110 inches **Overall Height:** 0.687 inches **Overall Width:** 0.687 inches **Environmental Protection:** Moisture resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.500 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.500 inches **Distance From Mounting Shoulder To Front Face:** 0.660 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** N single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Terminal Location:**

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

NSN 5935-01-031-1715

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Tab, solder lug single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shell Material Specification:

Qq-s-764, type 303, cond a federal specification single material response

Insert Material Specification:

Mil-p-19468 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

_

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.