NSN 5935-01-031-4593

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-031-4593 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.035 inches **Overall Diameter:** 0.688 inches **Distance From Mounting Shoulder To Front Face:** 0.830 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 400.0 single mating end single contact grouping Shell Type: Solid Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping or silver single mating end single contact grouping **Insert Material:** Plastic fluorocarbon single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:**

Copper alloy

NSN 5935-01-031-4593

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel alloy
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.005 gold grains, troy and 0.005 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0