NSN 5935-01-031-6993

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-031-6993 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, flush mount **Overall Length:** 1.061 inches **Overall Height:** 3.075 inches **Overall Width:** 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.783 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.436 inches **Distance From Mounting Shoulder To Front Face:** 0.060 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 67 all mating ends **Contact Removability:** Removable all mating ends all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 2nd mating end 2nd contact grouping Shell Type: Solid **Thread Size:** 0.112 inches **Terminal Location:** Back all mating ends all contact groupings **Contact Material:** Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic diallyl phthalate all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 2 military specification single treatment response all mating ends all contact groupings

NSN 5935-01-031-6993

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp all mating ends all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-591, alloy a380 federal specification single material response
Insert Material Specification:
Mil-m-19833, type gdi-30f military specification single material response all mating ends
Included Contact Quantity:
64 2nd mating end 2nd contact grouping
Included Contact Type:
Round pin all mating ends all contact groupings
Special Features:
Polarized in position 25
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.134 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.