## NSN 5935-01-031-6993

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-031-6993 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, flush mount **Overall Length:** 1.061 inches **Overall Height:** 3.075 inches **Overall Width:** 2.000 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.783 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.436 inches **Distance From Mounting Shoulder To Front Face:** 0.060 inches **Threaded Device Type:** Mounting hole **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 67 all mating ends **Contact Removability:** Removable all mating ends all contact groupings **Contact Maximum Current Rating In Amps:** 7.5 2nd mating end 2nd contact grouping Shell Type: Solid **Thread Size:** 0.112 inches **Terminal Location:** Back all mating ends all contact groupings **Contact Material:** Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:** 

Gold all mating ends all contact groupings

**Insert Material:** 

Plastic diallyl phthalate all mating ends

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 1, class 2 military specification single treatment response all mating ends all contact groupings

## NSN 5935-01-031-6993

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type:  |
|---|
| Crimp all mating ends all contact groupings   |
| Shell Material:   |
| Aluminum alloy  |
| Shell Surface Treatment:  |
| Cadmium   |
| Shell Surface Treatment Specification:  |
| Qq-p-416, type 2, cl 3 federal specification single treatment response                    |
| Shell Material Specification:   |
| Qq-a-591, alloy a380 federal specification single material response                       |
| Insert Material Specification:  |
| Mil-m-19833, type gdi-30f military specification single material response all mating ends |
| Included Contact Quantity:  |
| 64 2nd mating end 2nd contact grouping  |
| Included Contact Type:  |
| Round pin all mating ends all contact groupings   |
| Special Features:   |
| Polarized in position 25  |
| Precious Material And Location:   |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.134 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
| Mil-std (military Standard):  |
| Mil-g-45204 spec.   |
|   |