Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-031-7380

Body Style:
Single card
Overall Length:
4.281 inches
Overall Height:
0.512 inches
Overall Width:
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
4.031 inches
Board Accommodated Length:
3.587 inches single board
Board Accommodated Width:
Between 0.054 inches and 0.071 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
Bridged contacts inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Connector Locking Method:
Friction
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-750 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single
material response single mating end single contact grouping
Insert Material Specification:

# Insert Material Specification:

Mil-m-14, ty sdg military specification single material response single mating end or mil-p-19833, ty gdi-30 military specification single material response single mating end



Included Contact Quantity:

22 single mating end single contact grouping

#### Included Contact Type:

Leaf spring single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.022 gold grains, troy

### **Precious Material:**

Gold

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.