Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-031-7812

#### **Body Style:**

Straight type

**Overall Length:** 

6.355 inches

#### **Overall Height:**

0.571 inches

#### **Overall Width:**

Between 0.242 inches and 0.248 inches

## **Environmental Protection:**

Corrosion resistant and fungus resistant and vibration resistant and salt water resistant and shock resistant and humidity resistant

## **Unthreaded Mounting Hole Diameter:**

Between 0.096 inches and 0.101 inches

#### Distance Between Mounting Facility Centers:

6.065 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

## **Polarization Method:**

Fixed contact to contact

## **Connector Locking Method:**

Friction

Terminal Location:

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## Contact Surface Treatment:

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 type 2, cl 1 grade c military specification single treatment response single mating end single contact grouping

## Criticality Code Justification:

Feat

## Terminal Type:

Tab, solder lug single mating end single contact grouping

## **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping or qq-c-533 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single mating end single contact grouping or qq-c-750 federal specification single material response single material specification single material response single material specification single material spe

## **Insert Material Specification:**

Mil-m-14 ty gdi-30f or sdg-f military specification single material response single mating end or mil-m-24519 ty gpt-30f military specification single material response single mating end or mil-n-46174 cl 40 grade e military specification single material response single mating end

# NSN 5935-01-031-7812

Electrical Receptacle Connector - Page 2 of 2



**Included Contact Quantity:** 110 single mating end single contact grouping Included Contact Type: Flat socket single mating end single contact grouping **Special Features:** Pins no. 17 and 20 reamed to 0.067 in. Dia **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.110 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.