

View Online at <https://aerobasegroup.com/nsn/5935-01-031-7827>

Thread Class:

2a and 2a and 2a

Thread Direction:

Left-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.813 inches

Overall Diameter:

2.000 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Distance From Mounting Shoulder To Front Face:

1.109 inches

Mounting Facility Thickness:

Between 0.094 inches and 0.203 inches

Threaded Device Type:

Back shell and coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

22-22 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

135.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

18 and 10 and 18

Thread Size:

1.250 inches and 1.375 inches and 1.500 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Steel comp 302 or steel comp 303

Shell Surface Treatment:

Passivate

Shell Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Shell Material Specification:

Qq-s-763 federal specification single material response or astm-a582-75 assn standard single material response

Included Contact Quantity:

4 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.020 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef and double stub and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0