Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-031-8398

#### **Body Style:**

Straight shape, external coupling w/backshell

#### **Overall Length:**

1.009 inches

# **Overall Height:**

1.234 inches

#### **Overall Width:**

1.234 inches

#### **Environmental Protection:**

Moisture proof and salt water resistant and vibration proof

#### **Unthreaded Mounting Hole Diameter:**

#### 0.176 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 0.969 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

# 0.969 inches

Distance From Mounting Shoulder To Front Face:

#### 0.447 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

16-8 single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

#### **Insert Position In Deg:**

342.0

#### Shell Type:

Solid

# **Connector Locking Method:**

Bayonet pin

# **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
8 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Furnished items - mounting nut
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.008 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.