NSN 5935-01-031-9954

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-031-9954	
Thread Class:	
2a and 2a and 2a	
Thread Direction:	
Right-hand	
Body Style:	
Straight shape	
Overall Length:	
0.780 inches	
Overall Height:	
0.530 inches	
Overall Width:	
0.270 inches	
Environmental Protection:	
Moisture resistant and vibration resistant	
Distance Between Mounting Facility Centers:	
0.532 inches	
Threaded Device Type:	
Coupling facility and mounting stud	
Mating End Quantity:	
1	
Contact Position Arrangement Style:	
11 single mating end	
Contact Removability:	
Nonremovable single mating end single contact grouping	
Polarization Method:	
Jackscrew	
Connector Locking Method:	
Jackscrew-socket	
Thready Qty Per Inch (tpi):	
56 and 56 and 56	
Thread Size:	
0.086 inches and 0.086 inches and 0.086 inches	
Terminal Location:	
Rock single mating and single contact grouping	

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type sdg-f military specification single material response single mating end

NSN 5935-01-031-9954

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.