## NSN 5935-01-031-9960

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-031-9960

**Body Style:** 

Right angle type

**Overall Length:** 

3.090 inches

Overall Width:

Between 0.265 inches and 0.278 inches

**Environmental Protection:** 

Moisture resistant and salt water resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

0.062 inches

**Distance Between Mounting Facility Centers:** 

2.950 inches

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end

**Terminal Type:** 

Pin single mating end single contact grouping

**Contact Material Specification:** 

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-14, type sdg-f military specification single material response single mating end

**Included Contact Quantity:** 

54 single mating end single contact grouping

**Included Contact Type:** 

Hermaphrodite single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.054 gold grains, troy

## NSN 5935-01-031-9960

Electrical Receptacle Connector - Page 2 of 2



Gold
Test Data Document:
81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-55302/53 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

Fiig:

No

A039b0

Mil-std (military Standard):

Mil-m-14 spec.

**Precious Material:**