## NSN 5935-01-032-0848

Electrical Receptacle Connector - Page 1 of 2



· · · · · · · · · · · · · · · · · · ·
View Online at https://aerobasegroup.com/nsn/5935-01-032-0848
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.191 inches
Overall Height:
1.000 inches
Overall Width:
1.000 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.718 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.718 inches
Distance From Mounting Shoulder To Front Face:
0.562 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
10sl-3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:
0.375 inches
Thready Qty Per Inch (tpi):
24
Thread Size:

0.625 inches

## NSN 5935-01-032-0848

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic silicone mineral filled single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 1, class 2 federal specification single treatment response
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Hermetically sealed
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.