

View Online at https://aerobasegroup.com/nsn/5935-01-032-1844

| View Online at https://aerobasegroup.com/nsn/3333-01-032-1044 |
|--|
| Thread Class: |
| 2a and 2b |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Hood, side opening w/clamp |
| Overall Length: |
| 3.094 inches |
| Overall Height: |
| 2.484 inches |
| Overall Width: |
| 0.828 inches |
| Cable Entrance Diameter: |
| Between 0.063 inches and 0.563 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 50 single mating end |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Hood, side opening |
| Connector Locking Method: |
| Jackscrew-socket |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thread Size: |
| 0.138 inches and 0.138 inches |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Insert Material Specification: |
| Mil-m-14, ty sdg-f military specification single material response single mating end |
| Special Features: |
| Polarized in position a |
| Thread Series Designator: |
| Unc and unc |
| |

Electrical Plug Connector Body - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.