NSN 5935-01-032-3182

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-032-3182

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
0.688 inches
Overall Height:
0.530 inches
Overall Width:
0.188 inches
Environmental Protection:
Vibration resistant
Distance Between Mounting Facility Centers:
0.468 inches
Threaded Device Type:
Coupling facility and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
5 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Size:
0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 0 military specification 1st treatment response single mating end single contact grouping and qqs-365 federal
specification 2nd treatment response single mating end single contact grouping

NSN 5935-01-032-3182

Electrical Receptacle Connector - Page 2 of 2



Terminal	Type:
----------	-------

Solder well single mating end single contact grouping

Insert Material Specification:

Mil-p-19833, ty gdi-3 or gdi-30f military specification single material response single mating end

Included Contact Quantity:

5 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.005 gold grains, troy and 0.005 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc and unc

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.