Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-032-5394

Body Style:

Angle shape, pcb type

Overall Length:

5.650 inches

Overall Height:

0.359 inches

Overall Width:

0.550 inches

Environmental Protection:

Cold resistant and heat resistant and vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

5.400 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Guide Design And Location: D shape socket left-hand top at 9 oclock and d shape pin right-hand bottom at 9 oclock **Insert Material Specification:** Mil-m-24519 military specification single material response single mating end **Included Contact Quantity:** 90 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.090 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.