

View Online at <https://aerobasegroup.com/nsn/5935-01-033-1989>

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

3.655 inches

**Overall Height:**

0.658 inches

**Overall Width:**

0.330 inches

**Distance Between Mounting Facility Centers:**

3.405 inches

**Board Accommodated Length:**

2.952 inches single board

**Threaded Device Type:**

Mounting hole

**Board Accommodated Width:**

Between 0.054 inches and 0.071 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

1800.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Connector Locking Method:**

Friction

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14 military specification single material response single mating end

**Included Contact Quantity:**

36 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.036 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.