## NSN 5935-01-033-5335

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-033-5335

Body Style:

Right angle type

Overall Length:

3.050 inches

Overall Width:

O TOTAL TITLE

0.359 inches

Body Height:

0.525 inches

**Unthreaded Mounting Hole Diameter:** 

0.120 inches

**Distance Between Mounting Facility Centers:** 

2.800 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Terminal Location:** 

Side single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic polyphenylene single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Printed circuit single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-530 federal specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-m-24519 military specification single material response single mating end

**Included Contact Quantity:** 

44 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Special Features:** 

Round guide socket left-hand, square guide pin right hand; universal polarization type

## NSN 5935-01-033-5335

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.044 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.