

View Online at <https://aerobasegroup.com/nsn/5935-01-033-5821>

**Body Style:**

Right angle type

**Overall Length:**

3.690 inches

**Overall Width:**

0.360 inches

**Body Height:**

0.450 inches

**Environmental Protection:**

Moisture resistant and vibration resistant and shock resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:**

Between 0.105 inches and 0.108 inches

**Distance Between Mounting Facility Centers:**

1.437 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

1 row of contacts non-inserted board single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

300.0 single mating end single contact grouping

**Polarization Method:**

Guide pin/socket

**Connector Cable Strain Relief Method:**

Bracket

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-b-613 federal specification single material response single mating end single contact grouping or qq-b-625 federal specification single material response single mating end single contact grouping

**Included Contact Quantity:**

13 single mating end single contact grouping

**Included Contact Type:**

D-pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.013 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.